



PRESSALIT®

Pressalit Cera / Ceranova without cover 195
Standard toilet seat without cover incl. fixed hinge in stainless
steel

Item number

195000-BB2999
 VVS:615091000
 NRF:6190093
 RSK:7904440
 EAN:5708590161471

Pressalit Cera/Ceranova - without cover. A classic toilet seat with rounded edges and stunning shape. Specially designed for Ifö Cera and Ifö Ceranova.






Colour

White

Description

PRESSALIT toilet seat without cover, model "Cera/Ceranova", art. no. 195 made of colour ingrained duroplast with BB2 fixed hinge of stainless steel

- centre distance: 155 mm
- load - ring seat 240 kg
- for Ifö Cera/Ceranova toilet
- 10 year guarantee



Designer

Knud Holscher

Design year

1994

Materials

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.



PRESSALIT®

Pressalit Cera / Ceranova without cover 195
Standard toilet seat without cover incl. fixed hinge in stainless steel

Product capacity	Load - ring seat 240 kg
Weight	1,479 kg
Carton size	457x389x68 mm
Gross weight	2,279 kg
Crate size	469x401x348 mm
Weight per crate	11,395 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	<p>Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.</p> <p>In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.</p> <p>Subject to changes in the product range, technical changes and printing errors.</p>

pressalit.com
