

PRESSALIT.

Pressalit 956

Features Soft close


Item number 956000-DF9999


VVS:615065000 NRF:6190209 RSK:7821845


EAN:5708590348391

Colour White









Design type

Sandwich

Designer

Pressalit

Design year

2017

Materials

TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

POLYGIENE (only relevant for toilet seats with polygiene):

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.



PRESSALIT®

Pressalit 956

2,37 kg
488x388x72 mm
2,76 kg
500x400x368 mm
13,8 kg
5
12
60
Use a mild soap solution to clean the seat. Please take care that the seat and hinges a not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, ma sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Your Pressalit toilet seat is subject to a 10-year product warranty against presentation receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. In the event of complaints about defective materials and manufacturing defects and/or functional limitations ascertained within a 10-year period following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by identical or similar model. If the color is no longer available, Pressalit reserves its right replace the toilet seat by a similar model in the color white. Upon replacement or deliver of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com

PRESSALIT.